

WEGA Accessories

Accessories


DCATLABO12106XEN2

Gauges for WEGA Single or Dual Stage Series*

ALL GAUGES OXYGEN CLEANED, FREE OF OIL & GREASE

Standard process connection: G 1/4" male / acc. EN 562

Marking: bar; OXYGEN

 "Free of Oil & Grease", EN 562

Standard array of connection: 6 o'clock 







Diameter: 1.97 inches / 50 mm

*Further gauges are available on request








Gauge D43650-00G0036








Gauges Stainless Steel - Standard Stock items

| PART NUMBER | MAXIMUM PRESSURE | RED MARK | ARRAY OF CONNECTION |
|----------------------|--------------------|--------------------|---|
| Low Pressure | | | |
| D43650-00G0036 | 44 psi / 3 bar | 22 psi / 1.5 bar | 6 o'clock  |
| D43650-00G0056 | 73 psi / 5 bar | 44 psi / 3 bar | 6 o'clock  |
| D43650-00G0156 | 218 psi / 15 bar | 145 psi / 10 bar | 6 o'clock  |
| D43650-00G0266 | 363 psi / 25 bar | none | 6 o'clock  |
| High Pressure | | | |
| D43650-00G3156 | 4569 psi / 315 bar | 2900 psi / 200 bar | 6 o'clock  |
| D43650-00G4006 | 5801 psi / 400 bar | 4351 psi / 300 bar | 6 o'clock  |






Special Features for Stainless Steel gauges on request with additional charge

| CERTIFICATES FOR STAINLESS STEEL GAUGES | PART NUMBER ADDER |
|--|---|
| Cert 2.2 | 2 |
| Cert 3.1 | 3 |
| Calibration Cert | 4 |
| Cert 2.2 & Calibration Cert | 5 |
| Cert 3.1 & Calibration Cert | 6 |
| ARRAY OF CONNECTION | code The last character of part number defines the array of connection. Please replace it if you want to order a gauge different from standard. |
| 12 o'clock  | 0 |
| 3 o'clock  | 3 |
| 9 o'clock  | 9 |
| Central  | C |
| Frontring  | F |

Gauges Brass - Standard Stock items

| PART NUMBER | MAXIMUM PRESSURE | RED MARK | ARRAY OF CONNECTION |
|----------------------|--------------------|--------------------|---|
| Low Pressure | | | |
| D44150-00G0036 | 44 psi / 3 bar | 22 psi / 1.5 bar | 6 o'clock  |
| D44150-00G0056 | 73 psi / 5 bar | 44 psi / 3 bar | 6 o'clock  |
| D44150-00G0156 | 218 psi / 15 bar | 145 psi / 10 bar | 6 o'clock  |
| D44150-00G0406 | 580 psi / 40 bar | 290 psi / 20 bar | 6 o'clock  |
| High Pressure | | | |
| D44150-00G3156 | 4569 psi / 315 bar | 2900 psi / 200 bar | 6 o'clock  |
| D44150-00G4006 | 5801 psi / 400 bar | 4351 psi / 300 bar | 6 o'clock  |
| D44150-00G4016 | 5801 psi / 400 bar | none | 6 o'clock  |

Special Features for Stainless Steel gauges on request with additional charge

| CERTIFICATES FOR BRASS GAUGES | PART NUMBER ADDER |
|--|---|
| Calibration Cert | K |
| ARRAY OF CONNECTION | code The last character of part number defines the array of connection. Please replace it if you want to order a gauge different from standard. |
| 12 o'clock  | 0 |
| 3 o'clock  | 3 |
| 9 o'clock  | 9 |
| Central  | C |
| Frontring  | F |

Gauges for WEGA for Corrosive Gases and Purging Series

ALL GAUGES OXYGEN CLEANED, FREE OF OIL & GREASE AND SUITABLE FOR ECD APPLICATIONS

- Standard process connection:** G 1/4" NPT male / according ISO 5171
- Marking:** psi / bar
- Standard array of connection:** 6 o'clock
- Diameter:** 2.0 inches / 50.8 mm
- Material:** Stainless Steel
- Certificates:** calibration, 2.2 and 3.1 certificates available - please note when ordering



Gauge 4802-V060N

Gauges Stainless Steel - Standard Stock items

| PART NUMBER | MAXIMUM PRESSURE | ARRAY OF CONNECTION |
|------------------------------|--------------------|---------------------|
| Low Pressure (Outlet) | | |
| 4802-V060N | 60 psi / 4 bar | 6 o'clock |
| 4802-V100N | 100 psi / 7 bar | 6 o'clock |
| 4802-V200N | 200 psi / 14 bar | 6 o'clock |
| High Pressure (Inlet) | | |
| 4802-4000N | 4000 psi / 275 bar | 6 o'clock |

Metering Valves*

- Nominal diameter:** DN 2
- Inlet Connection:** G 1/4" male
- Outlet Connection:** 6 mm compression fitting + 6 mm hose connector

| PART NUMBER | MATERIAL | TYPE |
|--------------|-----------------|--------------------------|
| D43215-AR-05 | Brass | Diaphragm Metering Valve |
| D43216-AR-05 | Stainless Steel | Diaphragm Metering Valve |
| D41663-AO-05 | Brass | Needle Metering Valve |

*Please reference datasheets "Needle Metering Valves" and "Diaphragm Metering Valves" for detailed technical specifications



Needle Metering Valve
D41663



Diaphragm Metering Valve
D43216

Repair Kits WEGA

| PART NUMBER | DESCRIPTION |
|-------------|-----------------------------------|
| D43439 | Repair Kit WEGA 2 Brass |
| D43440 | Repair Kit WEGA 2 Stainless Steel |
| D43441 | Repair Kit WEGA 1 Brass |
| D43442 | Repair Kit WEGA 1 Stainless Steel |



WARNING! Do not attempt to select, install, use or maintain this product until you have read and fully understood the *TESCOM Safety, Installation and Operation Precautions*.

DCATLAB012106XEN2 © 2012 Emerson Process Management Regulator Technologies, Inc. All rights reserved. 05/2012.
Tescom, Emerson Process Management, and the Emerson Process Management design are marks of one of the Emerson Process Management group of companies. All other marks are the property of their respective owners.